

PRODUCT SPECIFICATIONS

POWER SPLITTER 698-3800MHz 4.3-10 FEMALE


MODEL JRT-SPx-0738-4310F

Features:

- Multiple-Band Frequency Ranges
- High Reliability
- Low PIM, low VSWR

Product Type	2-way Splitter	3-way Splitter	4-way Splitter
Model Number	SP2-0738-4310F	SP3-0738-4310F	SP4-0738-4310F
Frequency Range	698 - 3800MHz		
Insertion Loss	≤0.3dB	≤0.3dB	≤0.3dB
Distribution Loss	3.0dB	4.8dB	6.0dB
VSWR	<1.25		
PIM (IM3)	≤-153dBc @+43dBm*2		
Power Handling	300W		
Impedance	50Ω		
Connector Type	4.3-10 Female		
Applied Environment	Indoor or Outdoor, IP65		
Relative Humidity	5 to 95%		
Operating Temperature	-25 to +70°C		
Material	Cavity: Aluminum; Connector: Copper		
Processing	Silver plated inner conductor		
Dimension	213.6x67x25mm	233.2x67x25mm	233.2x67x46mm
Weight	0.38KG	0.49KG	0.54KG

2way Splitter:



3way Splitter:



4way Splitter:

